




REVISIONS		
REV.	DESCRIPTION	DATE
1	INITIAL RELEASE	7/18/2020



- ELECTRICAL:
 - IMPEDENCE 50Ω
 - FREQUENCY DC - 40GHz
 - VSWR 1.20 : 1 MAX
 - INSERTION LOSS 0.3dB MAX
- MATERIAL:
 - PIN: BERYLLIUM COPPER, GOLD PLATED
 - BODY: SUS 303, PASSIVATED
 - INSULATOR: PEI
- ENVIRONMENTAL:
 - TEMPERATURE RANGE: -45°C~+125°C
 - MATING CYCLES: >500
 - RoHS COMPLIANT
- INTERFACE STANDARD:
 - MIL-STD-348A



PROPRIETARY AND CONFIDENTIAL

THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF Coax Wizard. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF Coax Wizard IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN MM TOLERANCES: ANGULAR: MACH ± 1° BEND ± 1° INTEGER ± 3 ONE PLACE DECIMAL ± 1.0 TWO PLACE DECIMAL ± 0.50 INTERPRET GEOMETRIC TOLERANCING PER: ASME Y14.5	DRAWN	JX	07/18/20
	CHECKED	TC	07/18/20
	ENG APPR.	QW	07/18/20
	MFG APPR.		
	Q.A.		
MATERIAL		COMMENTS:	
FINISH		CUSTOMER OUTLINE DRAWING FOR REFERENCE ONLY	

**COAX WIZARD**

coaxwizard.com

TITLE:
ADAPTER, 2.92MM FEMALE,
2.92MM FEMALE, STRAIGHT,
BULKHEAD, L 20MM

SIZE	PN. NO.	REV
B	ADP-2.92F-2.92F-SB-20MM	1

SCALE: 1:2 WEIGHT: SHEET 1 OF 1